

**SEQUENCE LISTING**

**NOT APPLICABLE**

TITLE: "The Mini-Sweep" and its components.  
COMPONENTS: "The Mini-Lifter", "The Mini-Sweep Mounting Bracket"  
INVENTOR: Kevin King Irish  
INVENTED ON: Jan. 11, 2003  
ADDRESS: 20201 Gaukler St, St. Clair Shores, MI 48080-3772  
PHONE: (586) 773-5303 (w/voicemail)  
CITIZENSHIP: United States

## SPECIFICATION

(¶0001) "The Mini-Sweep" and its components are comparable to the non-motorized floor "sweepers" available.

(¶0002) "The Mini-Sweep"(Figure 1-Page 8) is composed of 2 assemblies ("The Mini-Sweep" and "The Mini-Lifter") and a single additional part ("The Mini-Sweep Storage/Mounting Bracket"). All of the components and assemblies, which make up "The Mini-Sweep", may be made/manufactured from any known, durable, high impact resistant plastic or resin manufactured through injection or blow-molding, or other plastic forming/molding manufacturing procedure. A small gauge, low tension metallic spring is used for "The Mini-Lifter" only. The basic dimensions to all components are:

- d) "The Mini-Sweep" (Figure 1) has 3 main components. The "cleaning head" where a "replaceable cleaning pad" is attached, is 6 inches in length, 2 inches in width and 1/8 inch thick. It has 2-1 inch by 3/8 inch, by 1/4 inch blocks for attaching to handle. There is a 3 1/8 inch by 1/8 diameter rod or dowel, also for attaching to handle. The handle is 18 inches in length, 1 inch wide and 3/8 inch thick. "The Mini-Sweep" is designed to clean small or low-clearance areas. Detailed dimensions on drawings.
- e) "The Mini-Lifter"(Figure 6-) has 3 components. The base is 3 inches long, 1 inch (at highest point), 1/4 inch (at lowest point) and 3/4 inch wide, with a material thickness of 1/8 inch. The "lever" mechanism is 3 inches in length (total), 7/8 inch in height (total), 7/16 inch in width, with a variable thickness from 1/8 inch to 1/2 inch. The base and lever attach pivotally on a 3/4 inch in length by 1/8 diameter rod or dowel. A small gauge, low tension, metallic spring is added to lever to allow lever to return to 'ready' condition. This assembly stores in the handle of "The Mini-Sweep". This device is designed to "lift" specific items for

cleaning under, with a minimum clearance of ¼ inch to ½ inch, manually.

Detailed dimensions on drawing.

- f) “The Mini-Sweep Mounting Bracket”(Figure 7) is a single piece, for storage of “The Mini-Sweep”, “The Mini-Lifter” and “replaceable cleaning pads” container/package, of a specific size. The basic dimensions are 6 ½ inches in height, 3 ¼ inches in width and 1 ¼ inch in depth. It has a “hook-type” feature that allows “The Mini-Sweep” to be stored. The Mounting Bracket can be installed behind doors, cabinet doors or any small space. Detailed dimensions on drawing.

(¶0003) All components listed above are to be considered when packaged together, as a single entity/unit/item. Only containers/packages of “replaceable cleaning pads” will be considered separate from “The Mini-Sweep” or its components.

(¶0004) Complete manufacturing reports, marketing reports, sales forecasts (projections) and patent attorney recommendation are available to QUALIFIED and AUTHORIZED inquiries ONLY AFTER OFFICIAL UNITED STATES PATENT NUMBER IS APPLIED AND ISSUED.

## Listing and summary of Photographs:

PAGE TITLE	DESCRIPTION
Minilifter.minisweep	B/W photo of Mini-Sweep components 1) Mini-Sweep 2) Storage/Mounting Bracket 3) Mini-Lifter
MINI-SWEEPa027	B/W photograph shown with 'cleaning pad box'
cleaningPADstorage1	Storage information
cleaningPADstorage2	Storage information
cleaningPADstorage3	Storage information
minisweepFLAT	Shown in 'storage' position
minisweepOPENTilted	Shown in 'open' position
storage BRACKET1	Side view of storage/mounting bracket
storage BRACKET2	Side view of storage/mounting bracket
minisweep.minilifter	Side view of complete assembly for storage
tv1	Showing cleaning on side of refrigerator
refrigerator1	Showing cleaning on side of refrigerator
stereo1	Showing cleaning under stereo component
minilifter1	Showing mini-lifter in 'open' position
minilifter2	showing mini-lifter in 'closed' position